## RCOA

Version 2.1 09/29/06

## **Motorcar Inspection Form**

Excursion \_\_\_\_\_ Location \_\_\_\_\_ Date \_\_\_\_\_

Operator Name \_\_\_\_\_ Motorcar Make \_\_\_\_\_ Railroad # (if available) \_\_\_\_

NARCOA Rule Book Certificate Number \_\_\_\_\_ NARCOA Current Insurance Number \_\_\_\_\_

					•
Items	Pre- Inspection	Sat	Unsat	Rule	I understand that "At all times each operator has the ultimate
On Board			-	-	responsibility for the safe
Charged Fire Extinguisher 2 lb (ABC)				I-18	condition of his/her motorcar
First Aid Kit				I-18	beyond any of the specifics of
Two Orange or Red Flags (16" sq)				I-14	the rules and standards". If
Current NARCOA Rule Book				II-10	
Operable Flashlight				I-18	allowed to operate in this
Compatible Tow Bar with Pins				I-10	excursion, I must correct any
Horn or Bell				I-16	unsatisfactory items indicated
Proper Brake Lever Travel				I-2	in order to participate in future
Front of Car			-		
Operable Front Headlight				I-12	excursions. These safety checks are not designed to be
Secure Front Hitch with 3/4" to 1" Hole				I-9	
Safety Glass or Polycarbonate Windshields				I-3	overly restrictive, but are to
Left Side of Car					insure a safe and enjoyable
Left Brake Shoe Thickness - Front/Rear					excursion for everyone.
Brakes Properly Adjusted				I-2	
Brake Cotter Pins Installed Properly					
Front Wheel Thickness and Profile				I-7	I certify that I have inspected
Rear Wheel Thickness and Profile				I-7	this motorcar and found it to
Axle Cotter Pins Installed - Front/Rear					meet all NARCOA standards
Rear of Car					as I have indicated on the Pre
Working Rear Red Tail Light				I-12	
Lever or Pedal Actuated Red Stop Light				I-13	Inspection column of this form
Secure Rear Hitch with 3/4" to 1" Hole				I-9	and have determined that this
Right Side of Car					motorcar is in a safe condition
Right Brake Shoe Thickness - Front/Rear					to operate on this excursion.
Brakes Properly Adjusted				I-2	
Brake Cotter Pins Installed Properly					
Front Wheel Thickness and Profile				I-7	
Rear Wheel Thickness and Profile				I-7	Operators Signature
Axle Cotter Pins Installed - Front/Rear					
TurnTable - If Installed					
Table Retracts min. of 2.5" above railhead				I-19	
Safety Lock on hydraulic turntables				I-19	
Audible Warning Device				I-19	Date
Optional - May not be required					
Mobile Radio					
USFS Approved Spark Arrestor					
Spare fuel secured properly				I-11	
Chock or Chain	1				
Front & Rear Lift Handles					
Safety Vest/Shirt					

You will \_\_\_\_\_, Will not, \_\_\_\_\_, be allowed to participate in this excursion.

Reviewed by: \_\_\_\_\_ Date \_\_\_\_\_